



VMS-F MULTISCREENING
FRONTAL BUCKET



SKID LOADER



MINI SKID



WHEEL LOADER



BACKHOE LOADER



TELEHANDLER




PATENTED













HB400





THE NEW MULTISCREENING BUCKET WITH THE NEW ROTARY DOUBLE DRUM CONCEPT FOR FRONTAL COUPLING AND MACHINES UP TO 14 TONS (30865 LB) IS SUITABLE FOR SELECTION DUTIES ON TURNED SOILS AND RESULTING MATERIALS. THE MATERIAL SIZE CHANGE – FROM 25 TO 60 MM (1 - 2,4 IN). - IS CONTROLLED DIRECTLY AND HYDRAULICALLY FROM THE CAB WITHOUT REPLACING ANY MECHANICAL PART THUS REDUCING THE WORK TIMES CONSIDERABLY.




	MOD.		VMS-F6		VMS-F8		VMS-F10	
 W/O COUPLER	KG (LB)		360	(794)	450	(992)	600	(1323)
 OPERATING	KG (LB)		550	(1213)	770	(1698)	1050	(2315)
 MIN.	MM (IN)		25	(1)	25	(1)	25	(1)
 MAX.	MM (IN)		65	(2,6)	65	(2,6)	65	(2,6)
 MAX.	L/MIN (GAL/ MIN)		80	(21)	80	(21)	80	(21)
 MAX.	BAR (PSI)		350	(5076)	350	(5076)	350	(5076)
 MAX.	L (GAL)		170	(44,9)	285	(75,3)	400	(105,7)


		VMS-F6	VMS-F8	VMS-F10
 N.		6	6	7
5  DC TEETH		DC 1 (KG 1,4)	DC 1 (KG 1,4)	DC 1 (KG 1,4)
5  DTE TEETH		DTE 13 (KG 1,7)	DTE 13 (KG 1,7)	DTE 13 (KG 1,7)



25 MM



INTERMEDIATE



65 MM

STANDARD TECHNICAL FEATURES

1 HB400 DRUMS

THE DRUMS CAN AFFORD HIGH WORK PACES THANKS TO THEIR HIGHLY RESISTANT MATERIAL THAT EXTENDS THEIR USEFUL LIFE.

2 AUTOMATIC SCREENING SYSTEM

THE NEW ROTARY DOUBLE DRUM CONCEPT WITH HYDRAULIC CONTROL FROM THE CAB ALLOWS TO SELECT THE MATERIAL SIZE, FROM 25 TO 60 MM (1 - 2,4 IN), WITHOUT STOPPING THE WORK CYCLE.

3 2 HOSES KIT

IT ALLOWS THE FUNCTIONING OF THE ROTATION AND HYDRAULIC SHIFTING OF THE SCREENING DRUMS ALSO ON MACHINES PROVIDED WITH A DOUBLE EFFECT LINE. CONTROL KIT WITH MAGNETS TO EASILY PUT IT INSIDE THE CAB.

4 OPERATING LOAD AND OPTIMAL WORKING CONDITION

OPTIONAL

5 DC TEETH DTE TEETH

6 HITCH FOR ARTICULATED LOADERS, BACKHOE LOADERS AND TELEHANDLER HANDLERS.

IT'S POSSIBLE TO ADD THE HITCH FOR ARTICULATED LOADERS, BACKHOE LOADERS AND TELEHANDLER HANDLERS TO THE SKID LOADER HITCH PROVIDED WITH THE STANDARD EQUIPMENT.